

CHATHAM COUNTY PURCHASING DEPARTMENT

ADDENDUM NO. 1 TO RFP 13-0025-7

FOR: Two (2) Detainee Transport Vehicles

PLEASE SEE THE FOLLOWING ADDITIONS, CLARIFICATIONS AND/OR CHANGES:

1. **Clarification:** Background of the project as it pertains to the size requirements. The detainee transport vehicles will be used to transport inmates from the Chatham County Detention Center to the Chatham County Judicial Courthouse, and occasionally to the State Prison in Reidsville, Georgia. There are approximately an average of 60 inmates transported per day. The sallyport or inmate transfer station is under the Chatham County parking garage next door to the Judicial Courthouse, and inmates are moved to the Courts via an underground tunnel. The vehicles entering the inmate transfer station go down an incline and enter through a double scissor door. Being underground, the maximum height, width, and length of the transport vehicle must be as described in the specifications or the vehicle will not be able to enter, turn around, or exit the transfer station.
2. **Clarification:** Section 2.28 Surety Requirements and Bonds - All proposers shall post a proposal/bid bond. Payment and Performance Bond shall be required upon award of a contract.
3. Replace Section V, Technical Specifications with **REVISED** Section V, Technical Specifications. (4 sheets)

THESE REVISED SHEETS REFLECT ALL QUESTIONS RECEIVED UP TO THIS TIME.

THE PROPOSAL RECEIPT DATE REMAINS 5:00PM APRIL 25, 2013.

*******THE BIDDER IS RESPONSIBLE FOR MAKING THE NECESSARY CHANGES AND MUST ACKNOWLEDGE RECEIPT OF ADDENDUM.*******

04/18/13
DATE


MARGARET H. JOYNER
PURCHASING AGENT
CHATHAM COUNTY

**SECTION V
TECHNICAL SPECIFICATIONS (REVISED)**

5.1 FEATURES

The overall size of the vehicle must not exceed:

Width: Eight (8) feet (maximum)
Length Twenty Five (25) feet (maximum)
Height: Nine (9) feet six (6) inches (9'6") maximum
Preferred height: Eight (8) feet
Minimum Twenty Two Inmate Capacity
with Two (2) additional Staff (Driver & Officer)

****ANSWERS TO THE QUESTIONS BELOW WILL BE EVALUATED AND BECOME PART OF THE SCORE IN SECTION 4.4.4.** PROPOSER SHALL PROVIDE DETAIL ONAN ATTACHMENT TO THEIR PROPOSAL FOR ALL "NO" RESPONSES.**

		Complies with Specifications	
		YES	NO
5.1.1	Capacity for minimum 22 detainees and two (2) officers	_____	_____
5.1.2	Configuration to include one (1) or two (2) steel containment segregation cages	_____	_____
5.1.3	Interior body to be equipped with solid steel bulkhead and sliding gate door.	_____	_____
 5.2 <u>CHASSIS</u>		 Complies with Specifications	
		YES	NO
5.2.1	Ford E-450 minimum	_____	_____
5.2.2	Chasis must meet federal standards for weight and axle load	_____	_____
5.2.3	14,500 GVWR minimum	_____	_____
5.2.4	6.8L EFI Triton V10 Engine (Gas)	_____	_____
5.2.5	TorqShift 5 speed automatic	_____	_____
5.2.6	Heavy duty radiator	_____	_____
5.2.7	Transmission – Auxiliary oil cooler	_____	_____

- 5.2.8 65 gallon Gas - Fuel Tank (approximately) _____
- 5.2.9 225 amps High Output, low RPM /
Heavy Duty Alternator (minimum) _____
- 5.2.10 3 heavy duty batteries system _____
- 5.2.11 Shuttle Bus Preparation Pkg. _____
- 5.2.12 Drive shaft guard _____
- 5.2.13 Vinyl Buckets Seats (Cab)
(available basic dark colors to be chosen at time of order) _____
- 5.2.14 Tilt Steering wheel _____
- 5.2.15 Pwr Windows / Locks _____
- 5.2.16 Cruise control _____
- 5.2.17 AM/FM radio _____
- 5.2.18 GPS Navigation (factory) _____
- 5.2.19 Cab running boards _____
- 5.2.20 4 Wheel ABS /Air Brakes _____
- 5.2.21 Spare Tire, Wheel & Jack _____
- 5.2.22 User Defined Switches _____
- 5.2.23 Factory Dual A/C compressor and Heat (Bendix 13.2 CFM) _____
- 5.2.24 Factory backup camera with color monitor _____
- 5.2.25 Back-up alarm _____
- 5.2.26 Dual rear wheels _____

5.3 CONVERSION DETAIL

Complies with
Specifications
YES NO

- 5.3.1 Body must meet requirements of ICE/DRO _____

Detention Standard on Transfer of Detainees
 (Security covers will be used where applicable)

- 5.3.2 Body constructed of 046 min. aluminum exterior side walls _____
- 5.3.3 2" double sided batted fiberglass insulation _____
- 5.3.4 5/8" Marine Tech 7-ply plywood floor (to include floor drains
with remote cables) _____
- 5.3.5 Air Ride Suspension _____
- 5.3.6 68,000 BTU minimum, A/C system
with heat coil (no roof top unit)(system to maximize comfort
for detainees) List BTU proposing _____
- 5.3.7 Curb side (inmate entry) door w/entry light & lighted steps _____
- 5.3.8 Air actuated sedan passenger entry door _____
- 5.3.9 Automatic heated moisture ejection valve for air tank _____
- 5.3.10 Lockable exterior storage compartment (curb side) _____
- 5.3.11 Windows – Transit type 4 per side mounted high _____
- 5.3.12 Rugged Molded Plastic Sets for detainees
(available basic dark colors to be chosen at time of order) _____
- 5.3.13 Vinyl/Rubber type floor _____
- 5.3.14 Interior high capacity LED type lights with protective cover _____
- 5.3.15 Emergency secondary interior lighting _____
- 5.3.16 Under-skirt storage _____
- 5.3.17 Gun safe/shotgun mount _____
- 5.3.18 Audio/video surveillance system with guard monitor _____
- 5.3.19 GPS monitoring system _____
- 5.3.20 Standard labeling and signage _____

5.3.21 Whelen emergency LED lighting (min. 12) and sirens _____

5.3.22 Pre-wire for communications antenna _____

5.4 STORAGE CABINET

Complies with
Specifications
YES NO

5.4.1 Mountable cabinet that will accommodate the following items: flashlights, extra handcuffs, flex cuffs and cutter, oleoresin capsicum (OC) spray, ICE/DRO approved batons, other authorized intermediate force (“non-lethal”, “non-deadly”) weapons, extinguisher, first aid kit, emergency triangle kit.

5.5 WARRANTY

Company/firm is to provide information on details of warranties.

5.6 DELIVERY

5.9.1 Scheduled delivery will be made to 65 Billy B. Hair Drive, Savannah, GA 31408

5.9.2 Vehicles will be delivered with not less than a half a tank of gas.