

CHATHAM COUNTY PURCHASING DEPARTMENT

ADDENDUM NO. 1 TO Bid No. 11-0011-5

**FOR: Bulldozer For Chatham County Fleet Operations**

=====

**PLEASE NOTE THE FOLLOWING ADDITIONS, CLARIFICATIONS AND/OR CHANGES:**

**Section 4.13:** Delete first sentence. Please change paragraph 4 to read "Trapezoidal hole shoes shall help prevent packing by allowing the sprocket to punch out dirt and debris".

**Section 4.13:** Change paragraph 6 to read "Extended Warranty shall be 60 months/8000 hours, front to back".

**Section 4.14:** Please note that undercarriage is to be included in Guaranteed Maintenance Program.

**Section 4.14:** Section 21 note that labor rates shall be the same for the entire guaranteed maintenance period.

**QUESTION:** Where will the bulldozer be located?


The County has four transfer stations:  
Wilmington Island  
Sallie Mood  
Chevis Road  
Sharon Road

---

**THE BID OPENING SHALL REMAIN 2PM, August 25, 2011.**

**THE BIDDER IS RESPONSIBLE FOR MAKING THE NECESSARY CHANGES AND MUST ACKNOWLEDGE RECEIPT OF ADDENDUM ON THEIR BID. REVISED PAGES 23 AND 24 ARE INCLUDED FOR YOUR CONVENIENCE.**

8/17/11  
DATE

  
\_\_\_\_\_  
Margaret H. Joyner  
PURCHASING AGENT  
CHATHAM COUNTY

Y\_\_\_ N\_\_\_ Extended Warranty shall be 60 months /8,000 hrs back to front

Y\_\_\_ N\_\_\_ 12 keys for every lock.

Y\_\_\_ N\_\_\_ Detail Repair Manual and a CD ROM Parts Book.

**4.14 GUARANTEED MAINTENANCE PROGRAM:** Chatham County shall consider two options regarding the purchase of this equipment. The County reserves the right to purchase the units out right with a standard or extended warranty, or with a guaranteed maintenance program including a buy-back provision. Each bidder shall indicate on the Bid Proposal Form the prices involved with the various options. If you do not offer a guaranteed maintenance plan, your bid on a straight purchase will be considered. The County will be the final and sole judge of the relative merits of all bids submitted:

1. Cost and services to be **included** in the guaranteed maintenance program are:
  2. All repairs and parts replacement not attributable to acts of God, accident damage, operator negligence or misuse, or vandalism.
  3. Scheduled preventive maintenance as recommended by the equipment manufacturer. This is to include normal periodic servicing, inspection and repair. The vendor is required to furnish all lubricants, fluids, filters and parts.
  4. Emergency service to make field repairs during hours when machine is in use.
  5. Stocking and maintaining an appropriate level of replacement parts.
6. Costs **not** to be **included** in the guaranteed maintenance program:
  7. Operators daily servicing and costs of lubricants and fluids used for this. Engine oil, transmission and hydraulic fluids, and lubricants must meet manufacturer's specifications.
  8. Refueling and cost of fuel.
  9. Transportation of machine to and from vendor's place of business.
  10. Cost of all repairs made under manufacturer's warranty.
  11. Cost of all repairs necessary as a result of an accident, acts of God, operator negligence or abuse or vandalism.
  12. The program shall be provided for five (5) years. The County shall have a renewal option for the sixth year with the cost to be negotiated between the County and the vendor.
  13. The cost of all services and parts provided by the vendor under the program will be billed to the County on a monthly basis. The County will pay for such parts and services until its total payments

Y\_\_\_ N\_\_\_ Quick disconnect fittings shall allow for fast diagnosis of power train and hydraulic oil systems.

Y\_\_\_ N\_\_\_ Winch components shall be serviceable with winch mounted on the tractor.

#### 4.12 MINIMUM SERVICE FILL CAPACITIES

Y\_\_\_ N\_\_\_ Fuel tank capacity shall not be less than 112 gal (424L).

Y\_\_\_ N\_\_\_ Cooling system capacity shall not be less than 18.5gal (76.8L).

Y\_\_\_ N\_\_\_ Engine crankcase capacity shall not be less than 7.4gal (28L).

Y\_\_\_ N\_\_\_ Power train capacity shall not be less than 38.5 gal (145.7L).

Y\_\_\_ N\_\_\_ Each final drive shall have a capacity of not less than 3.6 gal (13.6L).

Y\_\_\_ N\_\_\_ Each roller frame shall have a capacity of not less than 6.5 gal (24.6L).

Y\_\_\_ N\_\_\_ Hydraulic tank capacity shall not be less than 13.6gal (51.5L).

Y\_\_\_ N\_\_\_ Pivot shaft compartment capacity shall not be less than 1.3gal (1.9L).

#### 4.13 ADDITIONAL FEATURES

Y\_\_\_ N\_\_\_ Machine shall have an undercarriage system available that does not require a master style link and has sealed for life carriage style joints. The undercarriage shall also have center thread idlers to improve guiding and eliminate link scalloping. A rotating bushing design shall allow center thread idler and sprocket segments to be reuse through at least two undercarriage lives.

Y\_\_\_ N\_\_\_ Machine shall be painted in industry yellow color with black painted hood/cylinder/back of blade to reduce glare from lights while operating at night and also while operating in direct sunlight.

Y\_\_\_ N\_\_\_ Machine shall have a wireless fleet track system available to track location, machine hours, active and logged service codes and security alarms .This system shall be able to connect to other on board system, issue email or provide fuel consumption data.

Y\_\_\_ N\_\_\_ Trapezoidal hole shoes shall help prevent packing by allowing the sprocket to punch out dirt and debris.

Y\_\_\_ N\_\_\_ Standard Warranty shall be 12 months/unlimited hours